## Docket No.: 0941-1683PUS1

## AMENDMENTS TO THE CLAIMS

## 1-5. (Cancelled)

- 6. (Currently Amended) A gate drive device for a display, the open sequences for a plurality of scan lines in a panel being changed so that open sequences of the plurality of scan lines between the two adjacent gate drivers being the same, the drive device comprising:
  - a display panel comprising:
    - a first division panel comprising:
      - a first side;
      - a second side vertical with the first side;
      - a first scan line parallel with the first side; and
      - a second scan line parallel with the first scan line;
    - a second division panel comprising:
      - a third side parallel and adjacent with the first side;
      - a fourth side vertical with the third side:
      - a third scan line parallel and adjacent with the first scan line; and
      - a fourth scan line parallel with the third scan line;
    - a third division panel comprising:
      - a fifth side;
      - a sixth side vertical with the fifth side and adjacent with the second side;
      - a fifth scan line parallel with the fifth side; and
      - a sixth scan line parallel with the fifth scan line; and

Application No. 10/673,504 Amendment dated May 6, 2008

Reply to Advisory Action dated April 11, 2008

a fourth division panel comprising:

a seventh side parallel and adjacent with the fifth side;

a-an eighth side vertical with the seventh side and adjacent with the fourth

Docket No.: 0941-1683PUS1

side;

a seventh scan line parallel and adjacent with the fifth scan line; and

a-an eighth scan line parallel with the seventh scan line; and

a plurality of gate drivers being the gate drivers of the first, the second, the third, and the

fourth division panels;

a plurality of control circuits for connecting the data drivers and the gate drivers of the

first, the second, the third, and the fourth division panels; and

a timing control register connected to the plurality of control circuits by a plurality of

control lines;

wherein the timing control register is used for controlling the open timings of the first, the

second, the third, the fourth, the fifth, the sixth, the seventh, and the eighth scan lines, at a first

period, the first, the third, the fifth, and the seventh scan lines are opened at the same time, and at

a second period following the first period, the second, the fourth, the sixth, and the eighth scan

lines are opened at the same time; and

wherein, when the current frame finishes on the last scan line of each panel division at a

first time period the next frame will start with the first scan line of each panel division which is

at a second period after the first period.

3 JMS/DAB:tm